ARABLE SHAKAERATOR - FOLDING

Working Width 4.0m (13'0"), 5.0m (15'6")

Machine Features

- 4.0m and 5.0m Working widths
- Three-point linkage-mounting
- Hydraulically folding wings
- Compact transport position
- Unique hydraulic vibration unit
- Choice of leg configuration
- Breakback leg protection
- Choice of replaceable leg points
- Choice of rear attachments
- Deep soil conditioning
- Relieves soil compaction
- Improves drainage
- Increases crop yield

Markets

- Agricultural
- Contractors

Tractor Requirements

- 180hp minimum tractor horse power (dependent on model)

Seed Bed Preparation

Seed Bed Preparation

Descripion		4.0m	5.0m
Cutting width (m)	Maximum working width (m)	4.0 (13' 0")	5.0 (15' 6")
HP requirement	Minimum hp requirement of tractor	180	240
Weight (kg)	Weight of the machine	2048	3048
Attachment	Method of attachment to tractor	3 - point Cat 3 & 4	3 - point Cat 3 & 4
Depth control	Working height of rollers (mm)	118 - 600	118 - 600
Transport width	Maximum external width for transport (m)	2.52 - 2.82	2.52 - 2.83
Transport height	Maximum external height for transport (m)	2.1	2.1
Leg assembly number	Number of leg assemblies	8	10
Leg spacing	Protection of drive line (m)	0.5	0.5
Leg length	Length of leg assembly (mm)	750	750
No. of packer rollers	Number of rollers on the machine	2	2
Weight of rollers	Weight of packer rollers (kg)	480	580
Roller diameter	Exernal diameter of rollers (mm)	600	600
Scraper bar	Removes soil clods from roller	Standard	Standard